


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Albite Lux 325	6	325	400	345	86	50	5	112-121	39-48	26-35	120	310	403	484	1650	4,29	5,51	0,54	0,03	600X372X128
	6	325	500	445	86	50	5	112-121	39-48	26-35	153	396	515	618	2108	5,08	6,42	0,63	0,04	700X372X128
	6	325	600	545	86	50	5	112-121	39-48	26-35	188	486	632	758	2585	5,88	7,21	0,71	0,04	800X372X128
	6	325	700	645	86	50	5	112-121	39-48	26-35	215	555	721	865	2951	6,67	8,24	0,80	0,05	900X372X128
	6	325	800	745	86	50	5	112-121	39-48	26-35	240	620	806	968	3300	7,47	9,15	0,88	0,05	1000X372X128
	6	325	900	845	86	50	5	112-121	39-48	26-35	264	683	888	1065	3632	8,27	10,06	0,97	0,06	1100X372X128
	6	325	1000	945	86	50	5	112-121	39-48	26-35	287	742	965	1158	3948	9,06	10,97	1,05	0,06	1200X372X128
	6	325	1200	1145	86	50	5	112-121	39-48	26-35	330	852	1108	1329	4533	10,65	12,79	1,23	0,07	1400X372X128
6	325	1400	1345	86	50	5	112-121	39-48	26-35	379	978	1272	1526	5205	12,24	14,61	1,40	0,08	1600X372X128	

