


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Amazonite Max 635	10	635	575	605	137	100	4	N/A	N/A	N/A	304	785	1020	1224	4174	12,23	14,38	2,35	0,08	690X660X169
	10	635	675	605	137	100	4	N/A	N/A	N/A	347	896	1164	1397	4764	14,13	16,43	2,68	0,09	790X660X169
	10	635	775	605	137	100	4	N/A	N/A	N/A	388	1001	1302	1562	5327	16,04	18,50	3,02	0,10	890X660X169
	10	635	875	605	137	100	4	N/A	N/A	N/A	427	1102	1433	1720	5864	17,94	20,58	3,35	0,12	990X660X169
Amazonite Max 845	14	845	575	815	137	100	4	N/A	N/A	N/A	425	1098	1428	1714	5843	15,47	17,97	2,80	0,11	690X870X169
	14	845	675	815	137	100	4	N/A	N/A	N/A	485	1254	1630	1956	6670	17,90	20,59	3,19	0,12	790X870X169
	14	845	775	815	137	100	4	N/A	N/A	N/A	543	1402	1823	2187	7458	20,34	23,24	3,58	0,14	890X870X169
	14	845	875	815	137	100	4	N/A	N/A	N/A	597	1543	2006	2407	8209	22,77	25,86	3,97	0,15	990X870X169
Amazonite Max 1050	18	1050	575	1020	137	100	4	N/A	N/A	N/A	547	1412	1836	2203	7513	18,69	21,54	3,25	0,13	690X1075X169
	18	1050	675	1020	137	100	4	N/A	N/A	N/A	624	1612	2096	2515	8576	21,65	24,74	3,70	0,15	790X1075X169
	18	1050	775	1020	137	100	4	N/A	N/A	N/A	698	1803	2343	2812	9589	24,61	27,92	4,14	0,17	890X1075X169
	18	1050	875	1020	137	100	4	N/A	N/A	N/A	768	1984	2579	3095	10555	27,57	31,12	4,59	0,18	990X1075X169
Amazonite Max 1260	22	1260	575	1230	137	100	4	N/A	N/A	N/A	668	1726	2244	2693	9182	21,95	25,15	3,70	0,15	690X1285X169
	22	1260	675	1230	137	100	4	N/A	N/A	N/A	763	1970	2561	3074	10481	25,43	28,91	4,21	0,18	790X1285X169