


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70\text{ }^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m <sup>3</sup> )	Package Dimensions H x W x D (mm)
<b>Bamboo Max 720</b>	10	720	575	690	120	119	1	N/A	N/A	N/A	258	666	866	1039	3543	12,66	14,91	2,45	0,08	690X745X152
	10	720	675	690	120	119	1	N/A	N/A	N/A	294	760	988	1186	4045	14,59	17,01	2,78	0,09	790X745X152
	10	720	775	690	120	119	1	N/A	N/A	N/A	329	850	1105	1326	4523	16,52	19,12	3,11	0,11	890X745X152
	10	720	875	690	120	119	1	N/A	N/A	N/A	362	936	1217	1460	4978	18,45	21,22	3,44	0,12	990X745X152
<b>Bamboo Max 960</b>	14	960	575	930	120	119	1	N/A	N/A	N/A	361	933	1212	1455	4961	16,06	18,71	2,93	0,11	690X985X152
	14	960	675	930	120	119	1	N/A	N/A	N/A	412	1064	1384	1661	5663	18,53	21,39	3,32	0,12	790X985X152
	14	960	775	930	120	119	1	N/A	N/A	N/A	461	1190	1547	1857	6332	20,99	24,06	3,71	0,14	890X985X152
	14	960	875	930	120	119	1	N/A	N/A	N/A	507	1310	1703	2044	6969	23,46	26,75	4,10	0,15	990X985X152
<b>Bamboo Max 1200</b>	18	1200	575	1170	120	119	1	N/A	N/A	N/A	464	1199	1559	1870	6378	19,46	22,50	3,42	0,13	690X1225X152
	18	1200	675	1170	120	119	1	N/A	N/A	N/A	530	1369	1779	2135	7280	22,46	25,77	3,87	0,15	790X1225X152