


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output ΔT=30 °C (Watt)	Heat Output ΔT=50 °C (Watt)	Heat Output ΔT=60 °C (Watt)	Heat Output ΔT=70 °C (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m³)	Package Dimensions H x W x D (mm)
Besto 240	3	240	300	245	85	76	4	111-120	62-71	26-35	23	58	76	91	310	1,62	2,57	0,27	0,02	430X287X127
	3	240	400	345	85	76	4	111-120	62-71	26-35	31	79	103	124	423	1,87	2,92	0,31	0,02	530X287X127
	3	240	500	445	85	76	4	111-120	62-71	26-35	39	102	132	158	540	2,11	3,25	0,36	0,03	630X287X127
	3	240	600	545	85	76	4	111-120	62-71	26-35	48	125	162	194	662	2,36	3,50	0,40	0,03	730X287X127
	3	240	700	645	85	76	4	111-120	62-71	26-35	55	142	185	222	756	2,60	3,94	0,44	0,04	830X287X127
	3	240	900	845	85	76	4	111-120	62-71	26-35	68	175	227	273	930	3,09	4,63	0,53	0,04	1030X287X127
	3	240	1000	945	85	76	4	111-120	62-71	26-35	74	190	247	297	1011	3,34	4,97	0,57	0,05	1130X287X127
	3	240	1200	1145	85	76	4	111-120	62-71	26-35	84	218	284	341	1161	3,83	5,68	0,66	0,05	1330X287X127
	3	240	1400	1345	85	76	4	111-120	62-71	26-35	97	251	326	391	1333	4,32	6,37	0,74	0,06	1530X287X127
3	240	1600	1545	85	76	4	111-120	62-71	26-35	111	288	374	449	1531	4,81	7,05	0,83	0,07	1730X287X127	
3	240	1800	1745	85	76	4	111-120	62-71	26-35	128	330	430	515	1758	5,30	7,63	0,91	0,08	1930X287X127	

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Besto 1600	20	1600	300	245	85	76	4	111-120	62-71	26-35	150	389	505	606	2068	10,75	13,39	1,77	0,09	430X1647X127
	20	1600	400	345	85	76	4	111-120	62-71	26-35	205	530	689	826	2818	12,39	15,37	2,05	0,12	530X1647X127
	20	1600	500	445	85	76	4	111-120	62-71	26-35	262	677	880	1056	3600	14,03	17,35	2,34	0,14	630X1647X127
	20	1600	600	545	85	76	4	111-120	62-71	26-35	321	830	1079	1295	4415	15,66	19,20	2,63	0,16	730X1647X127
	20	1600	700	645	85	76	4	111-120	62-71	26-35	367	947	1232	1478	5040	17,30	21,31	2,91	0,18	830X1647X127
	20	1600	800	745	85	76	4	111-120	62-71	26-35	410	1059	1377	1653	5635	18,93	23,28	3,20	0,20	930X1647X127
	20	1600	900	845	85	76	4	111-120	62-71	26-35	451	1166	1516	1819	6203	20,57	25,27	3,48	0,22	1030X1647X127
Besto 1680	21	1680	300	245	85	76	4	111-120	62-71	26-35	158	408	531	637	2171	11,29	14,03	1,86	0,10	430X1727X127
	21	1680	400	345	85	76	4	111-120	62-71	26-35	215	556	723	868	2959	13,01	16,11	2,16	0,12	530X1727X127
	21	1680	500	445	85	76	4	111-120	62-71	26-35	275	711	924	1108	3780	14,73	18,17	2,46	0,14	630X1727X127
	21	1680	600	545	85	76	4	111-120	62-71	26-35	337	872	1133	1360	4636	16,45	20,14	2,76	0,17	730X1727X127
	21	1680	700	645	85	76	4	111-120	62-71	26-35	385	995	1293	1552	5292	18,16	22,32	3,06	0,19	830X1727X127
	21	1680	800	745	85	76	4	111-120	62-71	26-35	430	1112	1446	1735	5917	19,88	24,40	3,36	0,21	930X1727X127
	21	1680	900	845	85	76	4	111-120	62-71	26-35	474	1224	1592	1910	6513	21,60	26,49	3,66	0,23	1030X1727X127
Besto 1760	22	1760	300	245	85	76	4	111-120	62-71	26-35	165	428	556	667	2274	11,83	14,65	1,94	0,10	430X1807X127
	22	1760	400	345	85	76	4	111-120	62-71	26-35	225	583	757	909	3099	13,63	16,83	2,26	0,13	530X1807X127
	22	1760	500	445	85	76	4	111-120	62-71	26-35	288	744	968	1161	3960	15,43	19,00	2,57	0,15	630X1807X127
	22	1760	600	545	85	76	4	111-120	62-71	26-35	353	913	1187	1424	4857	17,23	21,05	2,89	0,17	730X1807X127
	22	1760	700	645	85	76	4	111-120	62-71	26-35	403	1042	1355	1626	5544	19,03	23,33	3,20	0,20	830X1807X127
	22	1760	800	745	85	76	4	111-120	62-71	26-35	451	1165	1515	1818	6199	20,83	25,52	3,52	0,22	930X1807X127
	22	1760	900	845	85	76	4	111-120	62-71	26-35	496	1283	1667	2001	6823	22,63	27,68	3,83	0,24	1030X1807X127
Besto 1840	23	1840	300	245	85	76	4	111-120	62-71	26-35	173	447	581	697	2378	12,37	15,29	2,03	0,11	430X1887X127
	23	1840	400	345	85	76	4	111-120	62-71	26-35	236	609	792	950	3240	14,25	17,54	2,36	0,13	530X1887X127
	23	1840	500	445	85	76	4	111-120	62-71	26-35	301	778	1012	1214	4140	16,13	19,81	2,69	0,16	630X1887X127
	23	1840	600	545	85	76	4	111-120	62-71	26-35	369	955	1241	1489	5078	18,02	21,97	3,02	0,18	730X1887X127
	23	1840	700	645	85	76	4	111-120	62-71	26-35	422	1090	1416	1700	5796	19,90	24,36	3,35	0,20	830X1887X127
	23	1840	800	745	85	76	4	111-120	62-71	26-35	471	1218	1584	1901	6481	21,78	26,63	3,68	0,23	930X1887X127
	23	1840	900	845	85	76	4	111-120	62-71	26-35	519	1341	1743	2092	7133	23,66	28,89	4,01	0,25	1030X1887X127
Besto 1920	24	1920	300	245	85	76	4	111-120	62-71	26-35	181	466	606	728	2481	12,90	15,91	2,12	0,11	430X1967X127
	24	1920	400	345	85	76	4	111-120	62-71	26-35	246	636	826	992	3381	14,86	18,27	2,46	0,14	530X1967X127
	24	1920	500	445	85	76	4	111-120	62-71	26-35	314	812	1056	1267	4320	16,83	20,64	2,81	0,16	630X1967X127
	24	1920	600	545	85	76	4	111-120	62-71	26-35	385	996	1295	1554	5298	18,79	22,88	3,15	0,19	730X1967X127
	24	1920	700	645	85	76	4	111-120	62-71	26-35	440	1137	1478	1774	6048	20,75	25,35	3,49	0,21	830X1967X127
	24	1920	800	745	85	76	4	111-120	62-71	26-35	492	1271	1653	1983	6763	22,72	27,72	3,84	0,24	930X1967X127
	24	1920	900	845	85	76	4	111-120	62-71	26-35	542	1399	1819	2183	7444	24,68	30,09	4,18	0,26	1030X1967X127
	24	1920	1000	945	85	76	4	111-120	62-71	26-35	589	1521	1978	2373	8092	26,64	32,29	4,52	0,29	1130X1967X127