



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Diamond Double 296	3	296	300	245	62	96	4	88-97	57-66	26-35	59	152	197	236	806	2,46	3,32	0,29	0,02	400X336X102
	3	296	400	345	62	96	4	88-97	57-66	26-35	80	207	269	322	1099	3,01	3,97	0,33	0,02	500X336X102
	3	296	500	445	62	96	4	88-97	57-66	26-35	102	264	343	412	1404	3,55	4,61	0,38	0,03	600X336X102
	3	296	600	545	62	96	4	88-97	57-66	26-35	125	324	421	505	1722	4,10	5,29	0,42	0,03	700X336X102
	3	296	700	645	62	96	4	88-97	57-66	26-35	143	369	480	576	1965	4,64	5,92	0,46	0,03	800X336X102
	3	296	800	745	62	96	4	88-97	57-66	26-35	160	413	537	644	2198	5,19	6,57	0,51	0,04	900X336X102
	3	296	900	845	62	96	4	88-97	57-66	26-35	176	455	591	709	2419	5,74	7,23	0,55	0,04	1000X336X102
	3	296	1000	945	62	96	4	88-97	57-66	26-35	191	494	643	771	2630	6,28	7,87	0,59	0,04	1100X336X102
	3	296	1200	1145	62	96	4	88-97	57-66	26-35	220	568	738	885	3019	7,37	9,18	0,68	0,05	1300X336X102
	3	296	1400	1345	62	96	4	88-97	57-66	26-35	252	652	847	1017	3467	8,47	10,49	0,76	0,06	1500X336X102
	3	296	1600	1545	62	96	4	88-97	57-66	26-35	290	748	973	1167	3980	9,54	11,77	0,85	0,06	1700X336X102
3	296	1800	1745	62	96	4	88-97	57-66	26-35	332	859	1117	1340	4570	10,63	13,21	0,93	0,07	1900X336X102	
3	296	2000	1945	62	96	4	88-97	57-66	26-35	382	986	1282	1539	5247	11,72	14,38	1,02	0,08	2100X336X102	

