


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Diamond Max 615	10	615	575	585	120	96	4	N/A	N/A	N/A	317	820	1066	1279	4362	12,18	14,25	2,33	0,07	690X640X152
	10	615	675	585	120	96	4	N/A	N/A	N/A	362	936	1217	1460	4979	14,09	16,32	2,66	0,08	790X640X152
	10	615	775	585	120	96	4	N/A	N/A	N/A	405	1047	1361	1633	5568	16,01	18,40	2,99	0,09	890X640X152
	10	615	875	585	120	96	4	N/A	N/A	N/A	446	1152	1498	1797	6128	17,92	20,45	3,33	0,10	990X640X152
Diamond Max 815	14	815	575	785	120	96	4	N/A	N/A	N/A	444	1148	1492	1791	6107	15,39	17,79	2,77	0,09	690X840X152
	14	815	675	785	120	96	4	N/A	N/A	N/A	507	1310	1704	2044	6971	17,84	20,44	3,16	0,11	790X840X152
	14	815	775	785	120	96	4	N/A	N/A	N/A	567	1465	1905	2286	7795	20,29	23,08	3,55	0,12	890X840X152
	14	815	875	785	120	96	4	N/A	N/A	N/A	624	1613	2097	2516	8579	22,73	25,71	3,94	0,13	990X840X152
Diamond Max 1015	18	1015	575	985	120	96	4	N/A	N/A	N/A	571	1476	1919	2303	7852	18,61	21,34	3,21	0,11	690X1040X152
	18	1015	675	985	120	96	4	N/A	N/A	N/A	652	1685	2190	2628	8962	21,59	24,55	3,66	0,13	790X1040X152
	18	1015	775	985	120	96	4	N/A	N/A	N/A	729	1884	2449	2939	10022	24,56	27,76	4,10	0,15	890X1040X152
	18	1015	875	985	120	96	4	N/A	N/A	N/A	802	2074	2696	3235	11031	27,54	30,95	4,55	0,16	990X1040X152
Diamond Max 1215	22	1215	575	1185	120	96	4	N/A	N/A	N/A	698	1804	2345	2814	9597	21,84	24,90	3,65	0,14	690X1240X152
	22	1215	675	1185	120	96	4	N/A	N/A	N/A	797	2059	2677	3212	10954	25,34	28,67	4,15	0,15	790X1240X152