


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axle Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	G Space Between Two Groups (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Mina 300	6 (3+3)	300	1100	285	46	149	1	182	70-79	37-46	24-33	262	520	676	812	2769	6,01	6,73	0,62	0,03	1200 x 340 x 55
	9 (3+3+3)	300	1700	285	46	149	1	166	70-79	37-46	24-33	396	786	1022	1227	4185	9,01	10,07	0,96	0,04	1800 x 340 x 55
Mina 400	6 (3+3)	400	1100	385	46	149	1	182	70-79	37-46	24-33	229	455	592	710	2422	6,94	7,88	0,62	0,04	1200 x 440 x 70
	9 (3+3+3)	400	1700	385	46	149	1	166	70-79	37-46	24-33	296	589	766	919	3134	10,41	11,78	0,96	0,06	1800 x 440 x 70
Mina 500	6 (3+3)	500	1100	485	46	149	1	182	70-79	37-46	24-33	295	586	762	915	3121	7,87	8,95	0,62	0,04	1200 x 540 x 55
	9 (3+3+3)	500	1700	485	46	149	1	166	70-79	37-46	24-33	362	720	936	1124	3833	11,80	13,40	0,96	0,06	1800 x 540 x 55
Mina 600	6 (3+3)	600	1100	585	46	149	1	182	70-79	37-46	24-33	267	530	689	827	2821	8,80	10,06	0,62	0,05	1200 x 640 x 55
	9 (3+3+3)	600	1700	585	46	149	1	166	70-79	37-46	24-33	370	734	955	1146	3908	13,20	15,06	0,96	0,07	1800 x 640 x 55