


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70\text{ }^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Nish Double 200	1	200	1600	1545	56	200	4	81-90	53-62	26-35	98	254	331	397	1353	7,79	9,54	0,34	0,04	1710X235X91
	1	200	1800	1745	56	200	4	81-90	53-62	26-35	113	292	380	456	1554	8,70	10,60	0,37	0,05	1910X235X91
Nish Double 404	2	404	300	245	56	200	4	81-90	53-62	26-35	40	103	134	161	548	3,72	4,69	0,31	0,02	410X439X91
	2	404	400	345	56	200	4	81-90	53-62	26-35	54	140	183	219	747	4,64	5,73	0,34	0,03	510X439X91
	2	404	500	445	56	200	4	81-90	53-62	26-35	69	179	233	280	955	5,55	6,74	0,37	0,03	610X439X91
	2	404	600	545	56	200	4	81-90	53-62	26-35	85	220	286	343	1171	6,46	7,75	0,40	0,03	710X439X91
	2	404	700	645	56	200	4	81-90	53-62	26-35	97	251	327	392	1336	7,37	8,78	0,43	0,04	810X439X91
	2	404	800	745	56	200	4	81-90	53-62	26-35	109	281	365	438	1494	8,28	9,80	0,46	0,04	910X439X91
	2	404	900	845	56	200	4	81-90	53-62	26-35	120	309	402	482	1645	9,19	10,83	0,48	0,05	1010X439X91
	2	404	1000	945	56	200	4	81-90	53-62	26-35	130	336	437	524	1788	10,11	11,86	0,51	0,05	1110X439X91
	2	404	1200	1145	56	200	4	81-90	53-62	26-35	149	386	502	602	2053	11,93	13,89	0,57	0,06	1310X439X91
	2	404	1400	1345	56	200	4	81-90	53-62	26-35	171	443	576	691	2357	13,75	15,94	0,63	0,07	1510X439X91
	2	404	1600	1545	56	200	4	81-90	53-62	26-35	197	509	661	794	2707	15,57	17,99	0,68	0,07	1710X439X91
2	404	1800	1745	56	200	4	81-90	53-62	26-35	226	584	759	911	3108	17,39	20,19	0,74	0,08	1910X439X91	

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output ΔT=30 °C (Watt)	Heat Output ΔT=50 °C (Watt)	Heat Output ΔT=60 °C (Watt)	Heat Output ΔT=70 °C (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m³)	Package Dimensions H x W x D (mm)
Nish Double 608	3	608	300	245	56	200	4	81-90	53-62	26-35	60	155	201	241	822	5,59	6,91	0,47	0,03	410X643X91
	3	608	400	345	56	200	4	81-90	53-62	26-35	82	211	274	329	1121	6,96	8,43	0,51	0,03	510X643X91
	3	608	500	445	56	200	4	81-90	53-62	26-35	104	269	350	420	1432	8,32	9,94	0,55	0,04	610X643X91
	3	608	600	545	56	200	4	81-90	53-62	26-35	128	330	429	515	1756	9,69	11,45	0,60	0,05	710X643X91
	3	608	700	645	56	200	4	81-90	53-62	26-35	146	377	490	588	2005	11,06	12,97	0,64	0,05	810X643X91
	3	608	800	745	56	200	4	81-90	53-62	26-35	163	421	548	657	2242	12,43	14,48	0,68	0,06	910X643X91
	3	608	900	845	56	200	4	81-90	53-62	26-35	179	464	603	724	2467	13,79	16,04	0,72	0,06	1010X643X91
	3	608	1000	945	56	200	4	81-90	53-62	26-35	195	504	655	787	2682	15,16	17,56	0,77	0,07	1110X643X91
	3	608	1200	1145	56	200	4	81-90	53-62	26-35	224	579	753	903	3080	17,90	20,60	0,85	0,08	1310X643X91
	3	608	1400	1345	56	200	4	81-90	53-62	26-35	257	665	864	1037	3536	20,63	23,63	0,94	0,09	1510X643X91
Nish Double 812	4	812	300	245	56	200	4	81-90	53-62	26-35	80	206	268	322	1097	7,45	8,95	0,62	0,04	410X847X91
	4	812	400	345	56	200	4	81-90	53-62	26-35	109	281	365	438	1494	9,28	10,98	0,68	0,04	510X847X91
	4	812	500	445	56	200	4	81-90	53-62	26-35	139	359	467	560	1909	11,10	12,98	0,74	0,05	610X847X91
	4	812	600	545	56	200	4	81-90	53-62	26-35	170	440	572	687	2342	12,92	14,97	0,79	0,06	710X847X91
	4	812	700	645	56	200	4	81-90	53-62	26-35	194	502	653	784	2673	14,75	17,01	0,85	0,07	810X847X91
	4	812	800	745	56	200	4	81-90	53-62	26-35	217	562	730	876	2989	16,57	18,99	0,91	0,08	910X847X91
	4	812	900	845	56	200	4	81-90	53-62	26-35	239	618	804	965	3290	18,39	21,00	0,97	0,08	1010X847X91
	4	812	1000	945	56	200	4	81-90	53-62	26-35	260	672	874	1049	3576	20,22	23,03	1,02	0,09	1110X847X91
	4	812	1200	1145	56	200	4	81-90	53-62	26-35	299	772	1003	1204	4106	23,86	27,03	1,14	0,11	1310X847X91
	4	812	1400	1345	56	200	4	81-90	53-62	26-35	343	886	1152	1383	4715	27,51	31,04	1,25	0,12	1510X847X91
Nish Double 1016	5	1016	300	245	56	200	4	81-90	53-62	26-35	100	258	335	402	1371	9,32	11,03	0,78	0,04	410X1051X91
	5	1016	400	345	56	200	4	81-90	53-62	26-35	136	351	457	548	1868	11,60	13,53	0,85	0,05	510X1051X91
	5	1016	500	445	56	200	4	81-90	53-62	26-35	174	449	583	700	2387	13,88	16,03	0,92	0,06	610X1051X91
	5	1016	600	545	56	200	4	81-90	53-62	26-35	213	550	715	858	2927	16,16	18,52	0,99	0,07	710X1051X91
	5	1016	700	645	56	200	4	81-90	53-62	26-35	243	628	817	980	3341	18,43	21,02	1,06	0,08	810X1051X91
	5	1016	800	745	56	200	4	81-90	53-62	26-35	272	702	913	1096	3736	20,71	23,52	1,13	0,09	910X1051X91
	5	1016	900	845	56	200	4	81-90	53-62	26-35	299	773	1005	1206	4112	22,99	26,02	1,21	0,10	1010X1051X91
	5	1016	1000	945	56	200	4	81-90	53-62	26-35	325	840	1092	1311	4470	25,27	28,52	1,28	0,11	1110X1051X91
	5	1016	1200	1145	56	200	4	81-90	53-62	26-35	373	965	1254	1505	5133	29,83	33,52	1,42	0,13	1310X1051X91
	5	1016	1400	1345	56	200	4	81-90	53-62	26-35	429	1108	1440	1728	5893	34,39	38,52	1,56	0,15	1510X1051X91
Nish Double 1220	6	1220	300	245	56	200	4	81-90	53-62	26-35	120	309	402	482	1645	11,17	13,07	0,93	0,05	410X1255X91
	6	1220	400	345	56	200	4	81-90	53-62	26-35	163	421	548	657	2242	13,91	16,07	1,02	0,06	510X1255X91
	6	1220	500	445	56	200	4	81-90	53-62	26-35	208	538	700	840	2864	16,64	19,05	1,10	0,07	610X1255X91
	6	1220	600	545	56	200	4	81-90	53-62	26-35	256	660	858	1030	3513	19,38	22,05	1,19	0,09	710X1255X91
	6	1220	700	645	56	200	4	81-90	53-62	26-35	292	754	980	1176	4009	22,11	25,04	1,27	0,10	810X1255X91
	6	1220	800	745	56	200	4	81-90	53-62	26-35	326	843	1096	1315	4483	24,85	28,03	1,36	0,11	910X1255X91
	6	1220	900	845	56	200	4	81-90	53-62	26-35	359	928	1206	1447	4935	27,58	31,02	1,45	0,12	1010X1255X91
	6	1220	1000	945	56	200	4	81-90	53-62	26-35	390	1008	1311	1573	5365	30,32	34,01	1,53	0,13	1110X1255X91
	6	1220	1200	1145	56	200	4	81-90	53-62	26-35	448	1158	1505	1806	6159	35,79	40,01	1,70	0,15	1310X1255X91
	6	1220	1400	1345	56	200	4	81-90	53-62	26-35	514	1329	1728	2074	7072	41,26	45,99	1,88	0,18	1510X1255X91
Nish Double 1424	7	1424	300	245	56	200	4	81-90	53-62	26-35	140	361	469	563	1919	13,04	15,13	1,09	0,06	410X1459X91
	7	1424	400	345	56	200	4	81-90	53-62	26-35	190	492	639	767	2615	16,23	18,61	1,19	0,07	510X1459X91
	7	1424	500	445	56	200	4	81-90	53-62	26-35	243	628	817	980	3341	19,42	22,10	1,29	0,09	610X1459X91
	7	1424	600	545	56	200	4	81-90	53-62	26-35	298	770	1001	1202	4098	22,61	25,58	1,39	0,10	710X1459X91
	7	1424	700	645	56	200	4	81-90	53-62	26-35	340	879	1143	1372	4678	25,80	29,06	1,49	0,11	810X1459X91
	7	1424	800	745	56	200	4	81-90	53-62	26-35	381	983	1278	1534	5230	28,99	32,54	1,59	0,13	910X1459X91
	7	1424	900	845	56	200	4	81-90	53-62	26-35	419	1082	1407	1688	5757	32,18	36,03	1,69	0,14	1010X1459X91
	7	1424	1000	945	56	200	4	81-90	53-62	26-35	455	1177	1529	1835	6259	35,37	39,51	1,79	0,15	1110X1459X91
	7	1424	1200	1145	56	200	4	81-90	53-62	26-35	523	1351	1756	2107	7186	41,75	46,49	1,99	0,18	1310X1459X91
	7	1424	1400	1345	56	200	4	81-90	53-62	26-35	600	1551	2016	2420	8251	48,13	53,45	2,19	0,21	1510X1459X91

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Nish Double 1628	8	1628	300	245	56	200	4	81-90	53-62	26-35	160	412	536	643	2193	14,90	17,18	1,24	0,07	410X1663X91
	8	1628	400	345	56	200	4	81-90	53-62	26-35	217	562	730	876	2989	18,55	21,17	1,36	0,08	510X1663X91
	8	1628	500	445	56	200	4	81-90	53-62	26-35	278	718	933	1120	3819	22,20	25,15	1,47	0,10	610X1663X91
	8	1628	600	545	56	200	4	81-90	53-62	26-35	341	880	1145	1373	4683	25,84	29,11	1,58	0,11	710X1663X91
	8	1628	700	645	56	200	4	81-90	53-62	26-35	389	1005	1306	1568	5346	29,49	33,08	1,70	0,13	810X1663X91
	8	1628	800	745	56	200	4	81-90	53-62	26-35	435	1124	1461	1753	5978	33,14	37,08	1,81	0,14	910X1663X91
	8	1628	900	845	56	200	4	81-90	53-62	26-35	479	1237	1608	1930	6580	36,78	41,05	1,93	0,16	1010X1663X91
	8	1628	1000	945	56	200	4	81-90	53-62	26-35	520	1345	1748	2098	7153	40,43	45,02	2,04	0,17	1110X1663X91
Nish Double 1832	9	1832	300	245	56	200	4	81-90	53-62	26-35	179	464	603	724	2467	16,77	19,24	1,40	0,07	410X1867X91
	9	1832	400	345	56	200	4	81-90	53-62	26-35	245	632	822	986	3362	20,87	23,71	1,52	0,09	510X1867X91
	9	1832	500	445	56	200	4	81-90	53-62	26-35	313	808	1050	1260	4296	24,97	28,18	1,65	0,11	610X1867X91
	9	1832	600	545	56	200	4	81-90	53-62	26-35	383	990	1288	1545	5269	29,07	32,64	1,78	0,13	710X1867X91
	9	1832	700	645	56	200	4	81-90	53-62	26-35	438	1131	1470	1764	6014	33,18	37,12	1,91	0,14	810X1867X91
	9	1832	800	745	56	200	4	81-90	53-62	26-35	489	1264	1643	1972	6725	37,28	41,59	2,04	0,16	910X1867X91
	9	1832	900	845	56	200	4	81-90	53-62	26-35	538	1391	1809	2171	7402	41,38	46,05	2,17	0,18	1010X1867X91
	9	1832	1000	945	56	200	4	81-90	53-62	26-35	585	1513	1966	2360	8047	45,48	50,31	2,30	0,19	1110X1867X91