


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Nish Double Lux 608	3	608	300	245	56	200	4	60-69	56-65	26-35	60	155	201	241	822	6,48	7,90	0,50	0,03	490X643X91
	3	608	400	345	56	200	4	60-69	56-65	26-35	82	211	274	329	1121	7,85	9,43	0,54	0,04	590X643X91
	3	608	500	445	56	200	4	60-69	56-65	26-35	104	269	350	420	1432	9,22	10,94	0,58	0,05	690X643X91
	3	608	600	545	56	200	4	60-69	56-65	26-35	128	330	429	515	1756	10,58	12,45	0,62	0,05	790X643X91
	3	608	700	645	56	200	4	60-69	56-65	26-35	146	377	490	588	2005	11,95	13,96	0,67	0,06	890X643X91
	3	608	700	645	56	200	4	60-69	56-65	26-35	146	377	490	588	2005	11,95	14,01	0,67	0,06	890X643X91
	3	608	800	745	56	200	4	60-69	56-65	26-35	163	421	548	657	2242	13,32	15,48	0,71	0,06	990X643X91
	3	608	900	845	56	200	4	60-69	56-65	26-35	179	464	603	724	2467	14,68	16,99	0,75	0,07	1090X643X91
	3	608	1000	945	56	200	4	60-69	56-65	26-35	195	504	655	787	2682	16,05	18,51	0,80	0,07	1190X643X91
	3	608	1200	1145	56	200	4	60-69	56-65	26-35	224	579	753	903	3080	18,79	21,54	0,88	0,09	1390X643X91
3	608	1400	1345	56	200	4	60-69	56-65	26-35	257	665	864	1037	3536	21,52	24,57	0,97	0,10	1590X643X91	

