


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70\text{ }^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Nish Line 200	1	200	1600	1545	62	200	4	81-90	53-62	26-35	98	254	331	397	1353	4,80	6,62	0,33	0,05	1720X240X102
	1	200	1800	1745	62	200	4	79-88	49-58	20-29	113	292	380	456	1554	5,34	7,65	0,36	0,05	1920X240X102
Nish Line 404	2	404	300	245	62	200	4	79-88	49-58	20-29	40	103	134	161	548	2,59	3,63	0,30	0,02	420X444X102
	2	404	400	345	62	200	4	79-88	49-58	20-29	54	140	183	219	747	3,13	4,29	0,32	0,03	520X444X102
	2	404	500	445	62	200	4	79-88	49-58	20-29	69	179	233	280	955	3,67	4,96	0,35	0,03	620X444X102
	2	404	600	545	62	200	4	79-88	49-58	20-29	85	220	286	343	1171	4,21	5,62	0,38	0,04	720X444X102
	2	404	700	645	62	200	4	79-88	49-58	20-29	97	251	327	392	1336	4,75	6,29	0,41	0,04	820X444X102
	2	404	800	745	62	200	4	79-88	49-58	20-29	109	281	365	438	1494	5,29	6,95	0,44	0,05	920X444X102
	2	404	900	845	62	200	4	79-88	49-58	20-29	120	309	402	482	1645	5,83	7,62	0,47	0,05	1020X444X102
	2	404	1000	945	62	200	4	79-88	49-58	20-29	130	336	437	524	1788	6,37	8,29	0,50	0,06	1120X444X102
	2	404	1200	1145	62	200	4	79-88	49-58	20-29	149	386	502	602	2053	7,45	9,61	0,55	0,06	1320X444X102
	2	404	1400	1345	62	200	4	79-88	49-58	20-29	171	443	576	691	2357	8,53	10,95	0,61	0,07	1520X444X102
2	404	1600	1545	62	200	4	79-88	49-58	20-29	197	509	661	794	2707	9,61	12,28	0,67	0,08	1720X444X102	
2	404	1800	1745	62	200	4	79-88	49-58	20-29	226	584	759	911	3108	10,69	13,85	0,72	0,09	1920X444X102	

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70\text{ }^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Nish Line 1832	9	1832	300	245	62	200	4	79-88	49-58	20-29	179	464	603	724	2467	11,68	14,62	1,32	0,09	420X1872X102
	9	1832	400	345	62	200	4	79-88	49-58	20-29	245	632	822	986	3362	14,11	17,43	1,45	0,10	520X1872X102
	9	1832	500	445	62	200	4	79-88	49-58	20-29	313	808	1050	1260	4296	16,54	20,25	1,58	0,12	620X1872X102
	9	1832	600	545	62	200	4	79-88	49-58	20-29	383	990	1288	1545	5269	18,97	23,05	1,71	0,14	720X1872X102
	9	1832	700	645	62	200	4	79-88	49-58	20-29	438	1131	1470	1764	6014	21,40	25,87	1,83	0,16	820X1872X102
	9	1832	800	745	62	200	4	79-88	49-58	20-29	489	1264	1643	1972	6725	23,83	28,68	1,96	0,18	920X1872X102
	9	1832	900	845	62	200	4	79-88	49-58	20-29	538	1391	1809	2171	7402	26,26	31,48	2,09	0,20	1020X1872X102
	9	1832	1000	945	62	200	4	79-88	49-58	20-29	585	1513	1966	2360	8047	28,69	33,91	2,22	0,22	1120X1872X102