


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	G Space Between Two Groups (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Perla Plus 300	10 (1+4+4+1)	300	865	285	32	30	20	145	73	57	41	115	228	297	356	1214	4,77	5,35	0,49	0,02	965 x 340 x 55
	12 (1+5+5+1)	300	995	285	32	30	20	155	73	57	41	136	268	349	419	1429	5,50	6,16	0,56	0,02	1095 x 340 x 55
	14 (1+4+4+4+1)	300	1190	285	32	30	20	145	73	57	41	160	317	413	495	1688	6,42	7,18	0,67	0,02	1290 x 340 x 55
	18 (1+4+4+4+4+1)	300	1530	285	32	30	20	148	73	57	41	206	407	530	635	2166	8,11	9,07	0,87	0,03	1630 x 340 x 55
Perla Plus 400	20 (1+3+3+3+3+3+3+1)	300	1690	285	32	30	20	120	73	57	41	228	451	587	704	2401	8,93	9,98	0,96	0,03	1790 x 340 x 55
	10 (1+4+4+1)	400	865	385	32	30	20	145	73	57	41	143	283	368	442	1508	5,55	6,28	0,49	0,02	965 x 440 x 55
	12 (1+5+5+1)	400	995	385	32	30	20	155	73	57	41	168	333	433	520	1774	6,44	7,26	0,56	0,03	1095 x 440 x 55
	14 (1+4+4+4+1)	400	1190	385	32	30	20	145	73	57	41	198	392	510	612	2087	7,50	8,46	0,67	0,03	1290 x 440 x 55
Perla Plus 500	18 (1+4+4+4+4+1)	400	1530	385	32	30	20	148	73	57	41	254	504	656	787	2684	9,48	10,68	0,87	0,04	1630 x 440 x 55
	20 (1+3+3+3+3+3+3+1)	400	1690	385	32	30	20	120	73	57	41	282	559	727	873	2977	10,44	11,76	0,96	0,04	1790 x 440 x 55
	10 (1+4+4+1)	500	865	485	32	30	20	145	73	57	41	171	339	441	529	1804	6,34	7,22	0,49	0,03	965 x 540 x 55
	12 (1+5+5+1)	500	995	485	32	30	20	155	73	57	41	203	401	522	626	2135	7,37	8,36	0,56	0,03	1095 x 540 x 55
Perla Plus 600	14 (1+4+4+4+1)	500	1190	485	32	30	20	145	73	57	41	238	472	614	737	2514	8,57	9,73	0,67	0,04	1290 x 540 x 55
	18 (1+4+4+4+4+1)	500	1530	485	32	30	20	148	73	57	41	305	606	788	946	3226	10,85	12,30	0,87	0,05	1630 x 540 x 55
	20 (1+3+3+3+3+3+3+1)	500	1690	485	32	30	20	120	73	57	41	339	672	874	1049	3578	11,96	13,54	0,96	0,05	1790 x 540 x 55
	10 (1+4+4+1)	600	865	585	32	30	20	145	73	57	41	201	398	518	621	2118	7,13	8,22	0,49	0,05	965 x 640 x 85
Perla Plus 600	12 (1+5+5+1)	600	995	585	32	30	20	155	73	57	41	238	471	613	735	2507	8,30	9,53	0,56	0,06	1095 x 640 x 85
	14 (1+4+4+4+1)	600	1190	585	32	30	20	145	73	57	41	280	554	721	865	2950	9,65	11,09	0,67	0,07	1290 x 640 x 85
	18 (1+4+4+4+4+1)	600	1530	585	32	30	20	148	73	57	41	359	712	926	1111	3789	12,21	14,01	0,87	0,09	1630 x 640 x 85
	20 (1+3+3+3+3+3+3+1)	600	1690	585	32	30	20	120	73	57	41	398	790	1027	1233	4205	13,47	15,43	0,96	0,10	1790 x 640 x 85