


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60\text{ }^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70\text{ }^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Sereno 306	3	306	1800	1745	29	100	3	72-98	57-83	44-70	180	465	605	726	2474	6,19	8,30	0,98	0,05	1990X331X61
	5	512	300	245	29	100	3	72-98	57-83	44-70	53	137	178	213	728	3,24	4,31	0,55	0,02	490X537X61
	5	512	400	345	29	100	3	72-98	57-83	44-70	72	186	242	291	991	3,71	4,89	0,63	0,02	590X537X61
Sereno 512	5	512	500	445	29	100	3	72-98	57-83	44-70	92	238	310	371	1267	4,19	5,50	0,70	0,03	690X537X61
	5	512	600	545	29	100	3	72-98	57-83	44-70	113	292	380	456	1554	4,66	6,09	0,77	0,03	790X537X61
	5	512	700	645	29	100	3	72-98	57-83	44-70	129	333	433	520	1773	5,14	6,69	0,84	0,03	890X537X61
	5	512	800	745	29	100	3	72-98	57-83	44-70	144	373	485	581	1983	5,61	7,28	0,91	0,04	990X537X61
	5	512	900	845	29	100	3	72-98	57-83	44-70	159	410	533	640	2183	6,08	7,86	0,98	0,04	1090X537X61
	5	512	1000	945	29	100	3	72-98	57-83	44-70	173	446	580	696	2373	6,56	8,46	1,06	0,04	1190X537X61
	5	512	1200	1145	29	100	3	72-98	57-83	44-70	198	512	666	799	2724	7,51	9,65	1,20	0,05	1390X537X61
	5	512	1400	1345	29	100	3	72-98	57-83	44-70	228	588	764	917	3128	8,45	10,83	1,34	0,06	1590X537X61
	5	512	1600	1545	29	100	3	72-98	57-83	44-70	261	675	878	1053	3591	9,36	11,98	1,48	0,06	1790X537X61
	5	512	1800	1745	29	100	3	72-98	57-83	44-70	300	775	1008	1209	4123	10,31	13,16	1,63	0,07	1990X537X61

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Sereno 718	7	718	300	245	29	100	3	72-98	57-83	44-70	74	191	249	299	1019	4,52	5,79	0,77	0,03	490X743X61
	7	718	400	345	29	100	3	72-98	57-83	44-70	101	261	339	407	1388	5,18	6,60	0,87	0,03	590X743X61
	7	718	500	445	29	100	3	72-98	57-83	44-70	129	333	433	520	1773	5,85	7,44	0,97	0,04	690X743X61
	7	718	600	545	29	100	3	72-98	57-83	44-70	158	409	532	638	2175	6,51	8,24	1,07	0,04	790X743X61
	7	718	700	645	29	100	3	72-98	57-83	44-70	181	467	607	728	2483	7,17	9,06	1,18	0,05	890X743X61
	7	718	800	745	29	100	3	72-98	57-83	44-70	202	522	678	814	2776	7,84	9,89	1,28	0,05	990X743X61
	7	718	900	845	29	100	3	72-98	57-83	44-70	222	574	747	896	3056	8,50	10,70	1,38	0,05	1090X743X61
	7	718	1000	945	29	100	3	72-98	57-83	44-70	242	624	812	974	3322	9,16	11,52	1,48	0,06	1190X743X61
	7	718	1200	1145	29	100	3	72-98	57-83	44-70	277	717	932	1118	3814	10,49	13,16	1,68	0,07	1390X743X61
	7	718	1400	1345	29	100	3	72-98	57-83	44-70	319	823	1070	1284	4379	11,82	14,81	1,88	0,08	1590X743X61
7	718	1600	1545	29	100	3	72-98	57-83	44-70	366	945	1229	1474	5028	13,11	16,40	2,08	0,09	1790X743X61	
7	718	1800	1745	29	100	3	72-98	57-83	44-70	420	1085	1411	1693	5773	14,43	18,03	2,28	0,10	1990X743X61	
Sereno 924	9	924	300	245	29	100	3	72-98	57-83	44-70	95	246	320	384	1310	5,81	7,28	0,99	0,03	490X949X61
	9	924	400	345	29	100	3	72-98	57-83	44-70	130	335	436	523	1785	6,66	8,32	1,12	0,04	590X949X61
	9	924	500	445	29	100	3	72-98	57-83	44-70	166	429	557	669	2280	7,52	9,38	1,25	0,04	690X949X61
	9	924	600	545	29	100	3	72-98	57-83	44-70	203	526	683	820	2796	8,37	10,43	1,38	0,05	790X949X61
	9	924	700	645	29	100	3	72-98	57-83	44-70	232	600	780	936	3192	9,22	11,45	1,51	0,06	890X949X61
	9	924	800	745	29	100	3	72-98	57-83	44-70	260	671	872	1047	3569	10,08	12,50	1,64	0,06	990X949X61
	9	924	900	845	29	100	3	72-98	57-83	44-70	286	739	960	1152	3929	10,93	13,55	1,77	0,07	1090X949X61
	9	924	1000	945	29	100	3	72-98	57-83	44-70	311	803	1044	1252	4271	11,78	14,60	1,90	0,07	1190X949X61
	9	924	1200	1145	29	100	3	72-98	57-83	44-70	357	922	1198	1438	4904	13,49	16,70	2,15	0,09	1390X949X61
	9	924	1400	1345	29	100	3	72-98	57-83	44-70	410	1058	1376	1651	5630	15,20	18,79	2,41	0,10	1590X949X61
9	924	1600	1545	29	100	3	72-98	57-83	44-70	470	1215	1580	1896	6464	16,84	20,81	2,67	0,11	1790X949X61	
9	924	1800	1745	29	100	3	72-98	57-83	44-70	540	1395	1814	2177	7422	18,55	22,91	2,92	0,12	1990X949X61	
Sereno 1130	11	1130	300	245	29	100	3	72-98	57-83	44-70	116	301	391	469	1601	7,10	8,76	1,21	0,04	490X1155X61
	11	1130	400	345	29	100	3	72-98	57-83	44-70	159	410	533	640	2181	8,14	10,05	1,37	0,05	590X1155X61
	11	1130	500	445	29	100	3	72-98	57-83	44-70	203	524	681	817	2787	9,19	11,32	1,53	0,05	690X1155X61
	11	1130	600	545	29	100	3	72-98	57-83	44-70	249	643	835	1002	3418	10,23	12,58	1,69	0,06	790X1155X61
	11	1130	700	645	29	100	3	72-98	57-83	44-70	284	733	953	1144	3901	11,27	13,86	1,84	0,07	890X1155X61
	11	1130	800	745	29	100	3	72-98	57-83	44-70	317	820	1066	1279	4362	12,31	15,13	2,00	0,07	990X1155X61
	11	1130	900	845	29	100	3	72-98	57-83	44-70	349	903	1173	1408	4802	13,36	16,41	2,16	0,08	1090X1155X61
	11	1130	1000	945	29	100	3	72-98	57-83	44-70	380	981	1276	1531	5220	14,40	17,68	2,32	0,09	1190X1155X61
	11	1130	1200	1145	29	100	3	72-98	57-83	44-70	436	1127	1465	1758	5993	16,49	20,23	2,63	0,10	1390X1155X61
	11	1130	1400	1345	29	100	3	72-98	57-83	44-70	501	1294	1682	2018	6881	18,57	22,76	2,94	0,12	1590X1155X61
	11	1130	1600	1545	29	100	3	72-98	57-83	44-70	575	1485	1931	2317	7901	20,59	25,25	3,26	0,13	1790X1155X61
11	1130	1800	1745	29	100	3	72-98	57-83	44-70	660	1705	2217	2660	9071	22,67	27,79	3,57	0,15	1990X1155X61	
Sereno 1336	13	1336	300	245	29	100	3	72-98	57-83	44-70	138	356	462	555	1892	8,38	10,25	1,43	0,05	490X1361X61
	13	1336	400	345	29	100	3	72-98	57-83	44-70	188	485	630	756	2578	9,61	11,74	1,62	0,05	590X1361X61
	13	1336	500	445	29	100	3	72-98	57-83	44-70	240	619	805	966	3293	10,85	13,26	1,81	0,06	690X1361X61
	13	1336	600	545	29	100	3	72-98	57-83	44-70	294	759	987	1185	4039	12,08	14,75	1,99	0,07	790X1361X61
	13	1336	700	645	29	100	3	72-98	57-83	44-70	335	867	1127	1352	4611	13,31	16,24	2,18	0,08	890X1361X61
	13	1336	800	745	29	100	3	72-98	57-83	44-70	375	969	1260	1512	5156	14,54	17,74	2,36	0,09	990X1361X61
	13	1336	900	845	29	100	3	72-98	57-83	44-70	413	1067	1387	1664	5675	15,77	19,24	2,55	0,10	1090X1361X61
	13	1336	1000	945	29	100	3	72-98	57-83	44-70	449	1160	1508	1809	6169	17,01	20,74	2,74	0,10	1190X1361X61
13	1336	1200	1145	29	100	3	72-98	57-83	44-70	515	1331	1731	2077	7083	19,47	23,75	3,11	0,12	1390X1361X61	
Sereno 1542	15	1542	300	245	29	100	3	72-98	57-83	44-70	159	410	533	640	2183	9,67	11,74	1,65	0,05	490X1567X61
	15	1542	400	345	29	100	3	72-98	57-83	44-70	216	559	727	872	2974	11,09	13,46	1,87	0,06	590X1567X61
	15	1542	500	445	29	100	3	72-98	57-83	44-70	276	714	929	1114	3800	12,52	15,20	2,08	0,07	690X1567X61
	15	1542	600	545	29	100	3	72-98	57-83	44-70	339	876	1139	1367	4661	13,94	16,92	2,30	0,08	790X1567X61
	15	1542	700	645	29	100	3	72-98	57-83	44-70	387	1000	1300	1560	5320	15,36	18,64	2,51	0,09	890X1567X61
	15	1542	800	745	29	100	3	72-98	57-83	44-70	433	1118	1454	1744	5949	16,78	20,36	2,73	0,10	990X1567X61
	15	1542	900	845	29	100	3	72-98	57-83	44-70	476	1231	1600	1920	6548	18,20	22,09	2,94	0,11	1090X1567X61
	15	1542	1000	945	29	100	3	72-98	57-83	44-70	518	1338	1740	2087	7118	19,63	23,82	3,15	0,12	1190X1567X61
15	1542	1200	1145	29	100	3	72-98	57-83	44-70	595	1536	1997	2397	8173	22,47	27,28	3,58	0,14	1390X1567X61	

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Sereno 1748	17	1748	300	245	29	100	3	72-98	57-83	44-70	180	465	604	725	2474	10,96	13,22	1,87	0,06	490X1773X61
	17	1748	400	345	29	100	3	72-98	57-83	44-70	245	634	824	989	3371	12,57	15,17	2,12	0,07	590X1773X61
	17	1748	500	445	29	100	3	72-98	57-83	44-70	313	810	1052	1263	4307	14,18	17,13	2,36	0,08	690X1773X61
	17	1748	600	545	29	100	3	72-98	57-83	44-70	384	993	1291	1549	5282	15,80	19,09	2,60	0,09	790X1773X61
	17	1748	700	645	29	100	3	72-98	57-83	44-70	439	1133	1473	1768	6029	17,41	21,04	2,85	0,10	890X1773X61
	17	1748	800	745	29	100	3	72-98	57-83	44-70	490	1267	1648	1977	6742	19,02	22,99	3,09	0,11	990X1773X61
	17	1748	900	845	29	100	3	72-98	57-83	44-70	540	1395	1813	2176	7421	20,63	24,95	3,33	0,12	1090X1773X61
Sereno 1954	17	1748	1000	945	29	100	3	72-98	57-83	44-70	587	1517	1971	2366	8067	22,24	26,89	3,57	0,13	1190X1773X61
	19	1954	300	245	29	100	3	72-98	57-83	44-70	201	520	676	811	2765	12,24	14,71	2,09	0,06	490X1979X61
	19	1954	400	345	29	100	3	72-98	57-83	44-70	274	708	921	1105	3768	14,04	16,89	2,36	0,08	590X1979X61
	19	1954	500	445	29	100	3	72-98	57-83	44-70	350	905	1176	1412	4813	15,84	19,07	2,64	0,09	690X1979X61
	19	1954	600	545	29	100	3	72-98	57-83	44-70	429	1110	1443	1731	5904	17,65	21,25	2,91	0,10	790X1979X61
	19	1954	700	645	29	100	3	72-98	57-83	44-70	490	1267	1647	1976	6739	19,45	23,43	3,18	0,11	890X1979X61
	19	1954	800	745	29	100	3	72-98	57-83	44-70	548	1416	1841	2210	7535	21,25	25,61	3,45	0,12	990X1979X61
19	1954	900	845	29	100	3	72-98	57-83	44-70	603	1559	2027	2432	8294	23,05	27,79	3,72	0,14	1090X1979X61	
19	1954	1000	945	29	100	3	72-98	57-83	44-70	656	1695	2203	2644	9016	24,85	29,97	3,99	0,15	1190X1979X61	