


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Seul Double 375	4	375	300	245	61	90	5	86-95	56-65	26-35	74	191	249	298	1018	3,34	4,28	0,37	0,02	400X415X101
	4	375	400	345	61	90	5	86-95	56-65	26-35	101	261	339	407	1387	4,12	5,17	0,43	0,03	500X415X101
	4	375	500	445	61	90	5	86-95	56-65	26-35	129	333	433	520	1772	4,90	6,08	0,49	0,03	600X415X101
	4	375	600	545	61	90	5	86-95	56-65	26-35	158	409	531	637	2174	5,68	6,98	0,55	0,03	700X415X101
	4	375	700	645	61	90	5	86-95	56-65	26-35	180	466	606	728	2481	6,46	7,89	0,60	0,04	800X415X101
	4	375	800	745	61	90	5	86-95	56-65	26-35	202	522	678	814	2774	7,24	8,78	0,66	0,04	900X415X101
	4	375	900	845	61	90	5	86-95	56-65	26-35	222	574	746	895	3054	8,02	9,68	0,72	0,05	1000X415X101
	4	375	1000	945	61	90	5	86-95	56-65	26-35	242	624	811	974	3320	8,80	10,58	0,77	0,05	1100X415X101
	4	375	1200	1145	61	90	5	86-95	56-65	26-35	277	716	931	1118	3811	10,36	12,37	0,89	0,06	1300X415X101
	4	375	1400	1345	61	90	5	86-95	56-65	26-35	318	823	1069	1283	4376	11,92	14,18	1,00	0,07	1500X415X101
	4	375	1600	1545	61	90	5	86-95	56-65	26-35	366	945	1228	1473	5025	13,45	15,95	1,12	0,08	1700X415X101
	4	375	1800	1745	61	90	5	86-95	56-65	26-35	420	1084	1410	1692	5769	15,01	17,87	1,23	0,08	1900X415X101
4	375	2000	1945	61	90	5	86-95	56-65	26-35	482	1245	1619	1942	6624	16,57	19,55	1,35	0,09	2100X415X101	

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Seul Double 565	6	565	300	245	61	90	5	86-95	56-65	26-35	111	287	373	448	1527	5,00	6,15	0,56	0,03	400X605X101
	6	565	400	345	61	90	5	86-95	56-65	26-35	151	391	508	610	2081	6,17	7,47	0,65	0,04	500X605X101
	6	565	500	445	61	90	5	86-95	56-65	26-35	193	500	650	780	2658	7,34	8,79	0,73	0,04	600X605X101
	6	565	600	545	61	90	5	86-95	56-65	26-35	237	613	797	956	3260	8,51	10,12	0,82	0,05	700X605X101
	6	565	700	645	61	90	5	86-95	56-65	26-35	271	700	909	1091	3722	9,68	11,44	0,90	0,05	800X605X101
	6	565	800	745	61	90	5	86-95	56-65	26-35	303	782	1017	1220	4161	10,85	12,77	0,99	0,06	900X605X101
	6	565	900	845	61	90	5	86-95	56-65	26-35	333	861	1119	1343	4580	12,02	14,09	1,08	0,07	1000X605X101
	6	565	1000	945	61	90	5	86-95	56-65	26-35	362	936	1217	1460	4979	13,19	15,42	1,16	0,07	1100X605X101
	6	565	1200	1145	61	90	5	86-95	56-65	26-35	416	1075	1397	1677	5717	15,53	18,06	1,33	0,08	1300X605X101
	6	565	1400	1345	61	90	5	86-95	56-65	26-35	478	1234	1604	1925	6564	17,87	20,71	1,50	0,10	1500X605X101
Seul Double 755	8	755	300	245	61	90	5	86-95	56-65	26-35	148	383	497	597	2036	6,67	8,17	0,75	0,04	400X795X101
	8	755	400	345	61	90	5	86-95	56-65	26-35	202	522	678	814	2774	8,23	9,92	0,86	0,05	500X795X101
	8	755	500	445	61	90	5	86-95	56-65	26-35	258	666	866	1039	3544	9,79	11,66	0,98	0,05	600X795X101
	8	755	600	545	61	90	5	86-95	56-65	26-35	316	817	1062	1275	4347	11,35	13,42	1,09	0,06	700X795X101
	8	755	700	645	61	90	5	86-95	56-65	26-35	361	933	1213	1455	4962	12,91	15,16	1,20	0,07	800X795X101
	8	755	800	745	61	90	5	86-95	56-65	26-35	404	1043	1356	1627	5549	14,47	16,92	1,32	0,08	900X795X101
	8	755	900	845	61	90	5	86-95	56-65	26-35	444	1148	1492	1791	6107	16,03	18,65	1,43	0,09	1000X795X101
	8	755	1000	945	61	90	5	86-95	56-65	26-35	483	1248	1623	1947	6639	17,59	20,41	1,55	0,09	1100X795X101
	8	755	1200	1145	61	90	5	86-95	56-65	26-35	555	1433	1863	2235	7623	20,71	23,90	1,78	0,11	1300X795X101
	8	755	1400	1345	61	90	5	86-95	56-65	26-35	637	1645	2139	2567	8752	23,83	27,40	2,01	0,13	1500X795X101
Seul Double 945	10	945	300	245	61	90	5	86-95	56-65	26-35	185	478	622	746	2545	8,34	10,04	0,93	0,04	400X985X101
	10	945	400	345	61	90	5	86-95	56-65	26-35	252	652	847	1017	3468	10,29	12,21	1,08	0,05	500X985X101
	10	945	500	445	61	90	5	86-95	56-65	26-35	322	833	1083	1299	4430	12,24	14,39	1,22	0,06	600X985X101
	10	945	600	545	61	90	5	86-95	56-65	26-35	395	1022	1328	1594	5434	14,19	16,56	1,36	0,07	700X985X101
	10	945	700	645	61	90	5	86-95	56-65	26-35	451	1166	1516	1819	6203	16,14	18,74	1,51	0,08	800X985X101
	10	945	800	745	61	90	5	86-95	56-65	26-35	505	1304	1695	2034	6936	18,09	20,90	1,65	0,09	900X985X101
	10	945	900	845	61	90	5	86-95	56-65	26-35	555	1435	1866	2239	7634	20,04	23,08	1,79	0,10	1000X985X101
	10	945	1000	945	61	90	5	86-95	56-65	26-35	604	1560	2028	2434	8299	21,99	25,24	1,93	0,11	1100X985X101
	10	945	1200	1145	61	90	5	86-95	56-65	26-35	693	1791	2329	2794	9529	25,89	29,59	2,22	0,13	1300X985X101
	10	945	1400	1345	61	90	5	86-95	56-65	26-35	796	2057	2674	3208	10940	29,79	33,94	2,51	0,15	1500X985X101
Seul Double 1135	12	1135	300	245	61	90	5	86-95	56-65	26-35	222	574	746	895	3054	10,01	11,91	1,12	0,05	400X1175X101
	12	1135	400	345	61	90	5	86-95	56-65	26-35	303	782	1017	1220	4161	12,35	14,52	1,29	0,06	500X1175X101
	12	1135	500	445	61	90	5	86-95	56-65	26-35	387	999	1299	1559	5317	14,69	17,11	1,46	0,08	600X1175X101
	12	1135	600	545	61	90	5	86-95	56-65	26-35	474	1226	1594	1912	6521	17,03	19,70	1,63	0,09	700X1175X101
	12	1135	700	645	61	90	5	86-95	56-65	26-35	541	1399	1819	2183	7443	19,37	22,29	1,81	0,10	800X1175X101
	12	1135	800	745	61	90	5	86-95	56-65	26-35	605	1565	2034	2441	8323	21,71	24,90	1,98	0,11	900X1175X101
	12	1135	900	845	61	90	5	86-95	56-65	26-35	666	1722	2239	2686	9161	24,05	27,49	2,15	0,12	1000X1175X101
	12	1135	1000	945	61	90	5	86-95	56-65	26-35	725	1872	2434	2921	9959	26,39	30,08	2,32	0,14	1100X1175X101
	12	1135	1200	1145	61	90	5	86-95	56-65	26-35	832	2149	2794	3353	11434	31,07	35,29	2,66	0,16	1300X1175X101
	12	1135	1400	1345	61	90	5	86-95	56-65	26-35	955	2468	3208	3850	13129	35,75	40,47	3,01	0,18	1500X1175X101
Seul Double 1325	14	1325	300	245	61	90	5	86-95	56-65	26-35	259	670	871	1045	3563	11,68	13,78	1,31	0,06	400X1365X101
	14	1325	400	345	61	90	5	86-95	56-65	26-35	353	913	1186	1424	4855	14,41	16,81	1,51	0,07	500X1365X101
	14	1325	500	445	61	90	5	86-95	56-65	26-35	451	1166	1516	1819	6203	17,14	19,83	1,71	0,09	600X1365X101
	14	1325	600	545	61	90	5	86-95	56-65	26-35	553	1430	1859	2231	7608	19,87	22,85	1,91	0,10	700X1365X101
	14	1325	700	645	61	90	5	86-95	56-65	26-35	632	1632	2122	2547	8684	22,60	25,87	2,11	0,12	800X1365X101
	14	1325	800	745	61	90	5	86-95	56-65	26-35	706	1825	2373	2847	9710	25,33	28,89	2,31	0,13	900X1365X101
	14	1325	900	845	61	90	5	86-95	56-65	26-35	778	2009	2612	3134	10688	28,06	31,90	2,51	0,14	1000X1365X101
	14	1325	1000	945	61	90	5	86-95	56-65	26-35	845	2184	2839	3407	11619	30,79	34,93	2,71	0,16	1100X1365X101
14	1325	1200	1145	61	90	5	86-95	56-65	26-35	970	2508	3260	3912	13340	36,25	40,97	3,11	0,18	1300X1365X101	
14	1325	1400	1345	61	90	5	86-95	56-65	26-35	1114	2879	3743	4492	15317	41,71	47,02	3,51	0,21	1500X1365X101	

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Seul Double 1515	16	1515	300	245	61	90	5	86-95	56-65	26-35	296	765	995	1194	4072	13,35	15,67	1,49	0,07	400X1555X101
	16	1515	400	345	61	90	5	86-95	56-65	26-35	404	1043	1356	1627	5549	16,47	19,11	1,72	0,08	500X1555X101
	16	1515	500	445	61	90	5	86-95	56-65	26-35	516	1333	1732	2079	7089	19,59	22,55	1,95	0,10	600X1555X101
	16	1515	600	545	61	90	5	86-95	56-65	26-35	633	1634	2125	2550	8694	22,71	25,99	2,18	0,11	700X1555X101
	16	1515	700	645	61	90	5	86-95	56-65	26-35	722	1866	2425	2910	9924	25,83	29,44	2,41	0,13	800X1555X101
	16	1515	800	745	61	90	5	86-95	56-65	26-35	807	2086	2712	3254	11097	28,95	32,88	2,64	0,15	900X1555X101
	16	1515	900	845	61	90	5	86-95	56-65	26-35	889	2296	2985	3582	12215	32,07	36,32	2,86	0,16	1000X1555X101
Seul Double 1705	16	1515	1000	945	61	90	5	86-95	56-65	26-35	966	2496	3245	3894	13279	35,19	39,77	3,09	0,18	1100X1555X101
	18	1705	300	245	61	90	5	86-95	56-65	26-35	333	861	1119	1343	4580	15,01	17,52	1,68	0,08	400X1745X101
	18	1705	400	345	61	90	5	86-95	56-65	26-35	454	1173	1525	1831	6242	18,52	21,38	1,94	0,09	500X1745X101
	18	1705	500	445	61	90	5	86-95	56-65	26-35	580	1499	1949	2339	7975	22,03	25,26	2,19	0,11	600X1745X101
	18	1705	600	545	61	90	5	86-95	56-65	26-35	712	1839	2390	2868	9781	25,54	29,12	2,45	0,13	700X1745X101
	18	1705	700	645	61	90	5	86-95	56-65	26-35	812	2099	2728	3274	11165	29,05	32,98	2,71	0,15	800X1745X101
	18	1705	800	745	61	90	5	86-95	56-65	26-35	908	2347	3051	3661	12484	32,56	36,86	2,96	0,16	900X1745X101
Seul Double 1895	18	1705	900	845	61	90	5	86-95	56-65	26-35	1000	2583	3358	4030	13741	36,07	40,72	3,22	0,18	1000X1745X101
	18	1705	1000	945	61	90	5	86-95	56-65	26-35	1087	2808	3651	4381	14938	39,58	44,60	3,48	0,20	1100X1745X101
	20	1895	300	245	61	90	5	86-95	56-65	26-35	370	957	1244	1492	5089	16,68	19,39	1,86	0,08	400X1935X101
	20	1895	400	345	61	90	5	86-95	56-65	26-35	505	1304	1695	2034	6936	20,58	23,68	2,15	0,10	500X1935X101
	20	1895	500	445	61	90	5	86-95	56-65	26-35	645	1666	2165	2599	8861	24,48	27,97	2,44	0,12	600X1935X101
	20	1895	600	545	61	90	5	86-95	56-65	26-35	791	2043	2656	3187	10868	28,38	32,26	2,72	0,14	700X1935X101
	20	1895	700	645	61	90	5	86-95	56-65	26-35	902	2332	3032	3638	12405	32,28	36,56	3,01	0,16	800X1935X101
Seul Double 1895	20	1895	800	745	61	90	5	86-95	56-65	26-35	1009	2608	3390	4068	13871	36,18	40,86	3,29	0,18	900X1935X101
	20	1895	900	845	61	90	5	86-95	56-65	26-35	1111	2870	3731	4477	15268	40,08	45,14	3,58	0,20	1000X1935X101
	20	1895	1000	945	61	90	5	86-95	56-65	26-35	1208	3120	4056	4868	16598	43,98	49,24	3,87	0,22	1100X1935X101