


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Sosa XL 236	3	236	300	245	62	76	4	62-71	43-52	26-35	52	133	174	208	710	2,45	2,69	0,26	0,02	400X276X102
	3	236	400	345	62	76	4	62-71	43-52	26-35	70	182	236	284	968	3,03	3,20	0,30	0,02	500X276X102
	3	236	500	445	62	76	4	62-71	43-52	26-35	90	232	302	362	1236	3,62	3,74	0,34	0,02	600X276X102
Sosa XL 316	4	316	300	245	62	76	4	62-71	43-52	26-35	69	178	231	278	947	3,21	3,41	0,34	0,02	400X356X102
	4	316	400	345	62	76	4	62-71	43-52	26-35	94	243	315	378	1290	3,97	4,09	0,40	0,02	500X356X102
	4	316	500	445	62	76	4	62-71	43-52	26-35	120	310	403	483	1648	4,70	4,78	0,46	0,03	600X356X102
	4	316	600	545	62	76	4	62-71	43-52	26-35	147	380	494	593	2021	5,48	5,46	0,51	0,03	700X356X102
	4	316	700	645	62	76	4	62-71	43-52	26-35	168	434	564	677	2307	6,23	6,13	0,57	0,03	800X356X102
	4	316	800	745	62	76	4	62-71	43-52	26-35	188	485	631	757	2580	6,96	6,81	0,63	0,04	900X356X102
	4	316	900	845	62	76	4	62-71	43-52	26-35	207	534	694	833	2840	7,74	7,49	0,68	0,04	1000X356X102
	4	316	1000	945	62	76	4	62-71	43-52	26-35	225	580	754	905	3087	8,49	8,16	0,74	0,04	1100X356X102
	4	316	1200	1145	62	76	4	62-71	43-52	26-35	258	666	866	1040	3545	10,00	9,51	0,86	0,05	1300X356X102
	4	316	1400	1345	62	76	4	62-71	43-52	26-35	296	765	995	1194	4070	11,54	10,87	0,97	0,06	1500X356X102
	4	316	1600	1545	62	76	4	62-71	43-52	26-35	340	878	1142	1370	4673	12,99	12,21	1,08	0,07	1700X356X102
4	316	1800	1745	62	76	4	62-71	43-52	26-35	390	1009	1311	1573	5365	14,50	13,69	1,20	0,07	1900X356X102	

Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Sosa XL 1836	23	1836	300	245	62	76	4	62-71	43-52	26-35	396	1023	1330	1596	5443	17,321547	17,201547	1,95	0,08	400X1876X102
	23	1836	400	345	62	76	4	62-71	43-52	26-35	540	1394	1813	2175	7418	21,334447	20,844447	2,28	0,1	500X1876X102
	23	1836	500	445	62	76	4	62-71	43-52	26-35	689	1782	2316	2779	9477	25,397347	24,507347	2,61	0,12	600X1876X102
	23	1836	600	545	62	76	4	62-71	43-52	26-35	846	2185	2841	3409	11623	29,460247	28,160247	2,94	0,14	700X1876X102
	23	1836	700	645	62	76	4	62-71	43-52	26-35	965	2494	3242	3891	13268	33,533147	31,813147	3,26	0,16	800X1876X102
	23	1836	800	745	62	76	4	62-71	43-52	26-35	1079	2789	3625	4351	14835	37,596047	35,466047	3,59	0,18	900X1876X102
	23	1836	900	845	62	76	4	62-71	43-52	26-35	1188	3070	3991	4789	16329	41,668947	39,128947	3,92	0,2	1000X1876X102
	23	1836	1000	945	62	76	4	62-71	43-52	26-35	1291	3337	4338	5206	17752	45,731847	42,771847	4,25	0,22	1100X1876X102
Sosa XL 1916	24	1916	300	245	62	76	4	62-71	43-52	26-35	413	1068	1388	1666	5680	18,015032	17,895032	2,03	0,08	400X1956X102
	24	1916	400	345	62	76	4	62-71	43-52	26-35	563	1455	1892	2270	7740	22,250232	21,710232	2,38	0,1	500X1956X102
	24	1916	500	445	62	76	4	62-71	43-52	26-35	719	1859	2417	2900	9889	26,515432	25,525432	2,72	0,12	600X1956X102
	24	1916	600	545	62	76	4	62-71	43-52	26-35	882	2280	2964	3557	12129	30,720632	29,320632	3,06	0,14	700X1956X102
	24	1916	700	645	62	76	4	62-71	43-52	26-35	1007	2603	3383	4060	13844	34,955832	33,145832	3,41	0,16	800X1956X102
	24	1916	800	745	62	76	4	62-71	43-52	26-35	1126	2910	3783	4540	15481	39,221032	36,951032	3,75	0,18	900X1956X102
	24	1916	900	845	62	76	4	62-71	43-52	26-35	1240	3203	4164	4997	17039	43,456232	40,766232	4,09	0,2	1000X1956X102
	24	1916	1000	945	62	76	4	62-71	43-52	26-35	1348	3482	4527	5432	18524	47,661432	44,571432	4,44	0,22	1100X1956X102
Sosa XL 1996	25	1996	300	245	62	76	4	62-71	43-52	26-35	430	1112	1446	1735	5916	18,758517	18,608517	2,12	0,09	400X2036X102
	25	1996	400	345	62	76	4	62-71	43-52	26-35	587	1516	1970	2364	8063	23,186017	22,576017	2,48	0,11	500X2036X102
	25	1996	500	445	62	76	4	62-71	43-52	26-35	749	1936	2517	3021	10301	27,593517	26,543517	2,83	0,13	600X2036X102
	25	1996	600	545	62	76	4	62-71	43-52	26-35	919	2375	3088	3705	12634	32,021017	30,511017	3,19	0,15	700X2036X102
	25	1996	700	645	62	76	4	62-71	43-52	26-35	1049	2711	3524	4229	14421	36,398517	34,478517	3,55	0,17	800X2036X102
	25	1996	800	745	62	76	4	62-71	43-52	26-35	1173	3031	3941	4729	16126	40,826017	38,456017	3,91	0,19	900X2036X102
	25	1996	900	845	62	76	4	62-71	43-52	26-35	1291	3337	4338	5205	17749	45,233517	42,423517	4,26	0,21	1000X2036X102
	25	1996	1000	945	62	76	4	62-71	43-52	26-35	1404	3627	4715	5659	19296	49,661017	46,231017	4,62	0,23	1100X2036X102