


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	G Space Between Two Groups (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Talia Plus 300	8 (3+5)	300	650	285	52	50	9	176	94-120	60-86	43-69	136	269	350	420	1433	3,93	4,44	0,37	0,02	750 x 340 x 85
	11 (4+7)	300	850	285	52	50	9	199	94-120	60-86	43-69	183	363	472	567	1934	5,21	5,83	0,48	0,03	950 x 340 x 85
	12 (3+4+5)	300	1050	285	52	50	9	174	94-120	60-86	43-69	209	414	539	646	2203	5,98	6,73	0,59	0,03	1150 x 340 x 85
	15 (4+5+6)	300	1250	285	52	50	9	186	94-120	60-86	43-69	256	508	661	793	2705	7,26	8,13	0,71	0,04	1350 x 340 x 85
	18 (3+4+5+6)	300	1550	285	52	50	9	168	94-120	60-86	43-69	311	617	803	963	3284	8,80	9,86	0,88	0,05	1650 x 340 x 85
	21 (3+4+6+8)	300	1750	285	52	50	9	175	94-120	60-86	43-69	359	712	926	1111	3789	10,07	11,25	0,99	0,05	1850 x 340 x 85
Talia Plus 400	8 (3+5)	400	650	385	52	50	9	176	94-120	60-86	43-69	178	353	459	551	1879	4,54	5,16	0,37	0,03	750 x 440 x 85
	11 (4+7)	400	850	385	52	50	9	199	94-120	60-86	43-69	242	479	623	748	2551	6,04	6,81	0,48	0,04	950 x 440 x 85
	12 (3+4+5)	400	1050	385	52	50	9	174	94-120	60-86	43-69	272	540	702	843	2875	6,89	7,82	0,59	0,04	1150 x 440 x 85
	15 (4+5+6)	400	1250	385	52	50	9	186	94-120	60-86	43-69	336	666	866	1039	3543	8,39	9,47	0,71	0,05	1350 x 440 x 85
	18 (3+4+5+6)	400	1550	385	52	50	9	168	94-120	60-86	43-69	407	807	1050	1259	4294	10,15	11,47	0,88	0,06	1650 x 440 x 85
	21 (3+4+6+8)	400	1750	385	52	50	9	175	94-120	60-86	43-69	470	932	1212	1454	4959	11,66	13,12	0,99	0,07	1850 x 440 x 85
Talia Plus 500	8 (3+5)	500	650	485	52	50	9	176	94-120	60-86	43-69	223	441	574	688	2347	5,14	5,88	0,37	0,03	750 x 540 x 85
	11 (4+7)	500	850	485	52	50	9	199	94-120	60-86	43-69	302	600	780	936	3192	6,86	7,79	0,48	0,04	950 x 540 x 85
	12 (3+4+5)	500	1050	485	52	50	9	174	94-120	60-86	43-69	339	672	874	1049	3578	7,79	8,90	0,59	0,05	1150 x 540 x 85
	15 (4+5+6)	500	1250	485	52	50	9	186	94-120	60-86	43-69	419	831	1081	1297	4423	9,52	10,81	0,71	0,06	1350 x 540 x 85
	18 (3+4+5+6)	500	1550	485	52	50	9	168	94-120	60-86	43-69	506	1004	1306	1567	5344	11,51	13,07	0,88	0,08	1650 x 540 x 85
	21 (3+4+6+8)	500	1750	485	52	50	9	175	94-120	60-86	43-69	586	1163	1512	1815	6190	13,24	14,98	0,99	0,08	1850 x 540 x 85
Talia Plus 600	8 (3+5)	600	650	585	52	50	9	176	94-120	60-86	43-69	268	532	692	830	2831	5,74	6,61	0,37	0,04	750 x 640 x 85
	11 (4+7)	600	850	585	52	50	9	199	94-120	60-86	43-69	365	725	943	1131	3857	7,69	8,77	0,48	0,05	950 x 640 x 85
	12 (3+4+5)	600	1050	585	52	50	9	174	94-120	60-86	43-69	408	809	1052	1263	4307	8,70	9,99	0,59	0,06	1150 x 640 x 85
	15 (4+5+6)	600	1250	585	52	50	9	186	94-120	60-86	43-69	505	1002	1303	1564	5334	10,65	12,15	0,71	0,07	1350 x 640 x 85
	18 (3+4+5+6)	600	1550	585	52	50	9	168	94-120	60-86	43-69	609	1210	1573	1888	6439	12,87	14,68	0,88	0,09	1650 x 640 x 85
	21 (3+4+6+8)	600	1750	585	52	50	9	175	94-120	60-86	43-69	706	1403	1824	2189	7465	14,82	16,85	0,99	0,10	1850 x 640 x 85