


Connection Types



Model	Section	Width W (mm)	Height H (mm)	A Axis Dimension (mm)	D Depth of the Product (mm)	F Tube Width (mm)	E Gap Between Two Tubes (mm)	G Space Between Two Groups (mm)	K Wall to Radiator Front (mm)	L Wall to Radiator Axis Center (mm)	M Wall to Radiator Back (mm)	Heat Output $\Delta T=30^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=50^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=60^{\circ}\text{C}$ (Watt)	Heat Output $\Delta T=70^{\circ}\text{C}$ (Watt)	BTU/h	Net Weight (kg)	Gross Weight (kg)	Water Volume (l)	Package Volume (m ³)	Package Dimensions H x W x D (mm)
Zeus 300	6 (3+3)	300	615	285	40	70	4	158	74-83	47-56	34-43	89	175	228	273	931	3,64	4,08	0,35	0,01	715 x 340 x 60
	9 (3+3+3)	300	1000	285	40	70	4	163	74-83	47-56	34-43	139	274	357	428	1460	5,52	6,19	0,57	0,02	1100 x 340 x 60
	12 (3+3+3+3)	300	1390	285	40	70	4	166	74-83	47-56	34-43	188	373	485	582	1985	7,42	8,31	0,79	0,03	1490 x 340 x 60
	15 (3+3+3+3+3)	300	1730	285	40	70	4	155	74-83	47-56	34-43	235	465	605	726	2476	9,18	10,27	0,98	0,04	1830 x 340 x 60
Zeus 400	6 (3+3)	400	615	385	40	70	4	158	74-83	47-56	34-43	115	228	297	356	1214	4,17	4,72	0,35	0,02	715 x 440 x 55
	9 (3+3+3)	400	1000	385	40	70	4	163	74-83	47-56	34-43	178	353	459	551	1879	6,32	7,15	0,57	0,03	1100 x 440 x 55
	12 (3+3+3+3)	400	1390	385	40	70	4	166	74-83	47-56	34-43	242	479	623	748	2551	8,49	9,59	0,79	0,04	1490 x 440 x 55
	15 (3+3+3+3+3)	400	1730	385	40	70	4	155	74-83	47-56	34-43	302	598	778	933	3182	10,52	11,87	0,98	0,04	1830 x 440 x 55
Zeus 500	6 (3+3)	500	615	485	40	70	4	158	74-83	47-56	34-43	143	283	368	442	1508	4,70	5,36	0,35	0,02	715 x 540 x 55
	9 (3+3+3)	500	1000	485	40	70	4	163	74-83	47-56	34-43	220	436	567	681	2323	7,12	8,11	0,57	0,03	1100 x 540 x 55
	12 (3+3+3+3)	500	1390	485	40	70	4	166	74-83	47-56	34-43	297	590	767	921	3141	9,55	10,88	0,79	0,04	1490 x 540 x 55
	15 (3+3+3+3+3)	500	1730	485	40	70	4	155	74-83	47-56	34-43	371	736	957	1149	3919	11,85	13,47	0,98	0,05	1830 x 540 x 55
Zeus 600	6 (3+3)	600	615	585	40	70	4	158	74-83	47-56	34-43	172	341	444	532	1815	5,24	6,01	0,35	0,03	715 x 640 x 55
	9 (3+3+3)	600	1000	585	40	70	4	163	74-83	47-56	34-43	264	523	680	816	2783	7,92	9,08	0,57	0,04	1100 x 640 x 55
	12 (3+3+3+3)	600	1390	585	40	70	4	166	74-83	47-56	34-43	355	705	917	1100	3751	10,62	12,17	0,79	0,05	1490 x 640 x 55
	15 (3+3+3+3+3)	600	1730	585	40	70	4	155	74-83	47-56	34-43	443	880	1144	1373	4682	13,19	15,08	0,98	0,06	1830 x 640 x 55